

# DST-1

## Temperature Device Station

The TrolMaster DST-1 Temperature Device Station modules allow the user to easily connect and control standard heating or cooling devices to the Hydro-X. Any heating or cooling device that is 10-amps at 120 volts or less can be controlled by the DST-1.



## Specifications

### DST-1

#### Input Voltage

Voltage 100-240V~, 50/60Hz

#### Output Current

Current 10A

#### Output Voltage

Voltage 100-240V~, 50/60Hz

#### Working Environments

Temperature 32-122°F (0-50°C)

Humidity ≤90%

#### Package Content

Temperature Device Station 1pc

16ft RJ12 Cable 1pc

4ft RJ12 Cable 1pc

RJ12 T-Splitter 1pc

#### Package Dimensions

Size 3.35"/85mm (L) x  
3.15"/80mm (W) x  
3.54"/90mm (H)

Gross Weight 11.99oz /340g

## LED Indicator Status

LED Indicator	Module Status
Fast Blinking Green	Module is not addressed to the main controller, OR module does not have a good connection to the main controller. <b>*Note:</b> Press the small address/link button on the module when first installed.
Slow Blinking Green	Module is addressed and connected to the main controller, and is currently turned OFF.
Solid Green	Module is addressed, connected, and currently turned ON.
Blinking Red	Module is overloaded. Reset the overload by unplugging the module from powersource .

## Link Up

### DST-1

#### CONNECTION DIAGRAM

(HCS-1/HCS-2/HCS-3)

